




## 240

Husqvarna 240 is ideal for jobs like pruning, lighter cutting tasks and hobby work. Easy to start and operate, thanks to built-in Husqvarna features like ergonomic design, facilitating technology and powerful X-Torq® engine with low emissions.




### AIR INJECTION

Centrifugal air cleaning system removes larger dust and debris particles before reaching the air filter. This results in reduced air filter cleanings and improved engine life.



### X-TORQ®

Delivers lower fuel consumption and reduced exhaust emission levels in accordance with the world's most stringent environmental regulations.



### COMBINED CHOKE/STOP CONTROL

Allows for easier starting and reduces the risk of engine flooding.



### SIDE-MOUNTED CHAIN TENSIONER

Easier access to chain tensioning device.

## Features

- LowVib® sparing the user's arms and hands
- Fuel pump for easy starting
- Increased safety, inertia activated chain brake

## Technical data cylinder displacement

	<b>38.2 cc</b>
Power output	2 hp
Horsepower	2 hp(M)
Idling speed	3000 rpm
Maximum power speed	9000 rpm
Cylinder bore	1.57 inch
Cylinder stroke	1.26 inch
Ignition system	IIDA
Ignition module air gap	0.01 "
Spark plug	Champion RCJ7Y
Electrode gap	0.02 "
Carburetor model name	ZAMAW-33
Fuel tank volume	0.14 US pint
Oil tank volume	0.09 US pint
Oil pump type	Fixed flow
Oil pump capacity	8-8 ml/min
Chain pitch	.325" / 3/8"
Recommended bar length, min-max	13"-16"
Chain speed at max power	53.48 fts
Equivalent vibration level (ahv, eq) front / rear handle	2.1/2.7 m/s <sup>2</sup>
Sound pressure level at operators ear	100.7 dB(A)
Sound power level, guaranteed (LWA)	113 dB(A)
Weight (excl. cutting equipment)	10.3 lbs

## ARTICLES

952 80 21-54	16" - 3/8 - SN - EPA - US, CA	<b>\$ 199.95</b>
--------------	-------------------------------	------------------

